

Industrial vacuum cleaner 55 S

Dry vacuum cleaner useful in most applications with dust from tools or cleaning operations within industry



The 55S is a efficient three phase compact industrial vacuum cleaner. A very efficient, economical, low noise level and easy to handle dry vacuum. The vacuum is very easy to dismantle and clean. This portable dust collector has long filter lifetime 4-6000 h (with bag filter). The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.

- Long filter lifetime (4-6000 hours)
- Low noise level
- · Micro filter as option

Product name	Industrial vacuum cleaner 55 S
Noise level (dB(A))	72
Protection class	IP 55
Filter efficiency (%)	99
Installation	[Indoor]
Material	Casing in sheet metal
Filter cleaning method	[ReverseAirPulse]
Application	[dust], [granulate], [fumes], [swarf]
Working pressure (psi)	30
Dustbin volume (gal)	7,3
Max Airflow (cfm)	210
Hose Diameter (in)	2,01
Hose length (ft.)	16.4 ft
Frequency (Hz)	60
No of phases	3
Filter type	[bag]
Number of filter elements	1
Filter material	Polypropylene
Noise level (dB(A))	72
Max vakuum (in. wg)	-118
Weight (lbs)	223
Hose length (m)	16,4
Hose diameter (mm)	2
Power (Hp)	8.4 (6.3 Kw)
Note	Heavy duty cleaning equipment included











Fumes

Swarf

Dust



Industrial vacuum cleaner 55 S

[image]	Power Voltage (V)	[model]
	230	40056030*
	460	40056040*

^{*}Heavy duty cleaning equipment included



Industrial vacuum cleaner 55 S

	[accessory]	[partno]
	Microfilter D= 140 x 500	40114120
	Hand nozzle, hard brush Ø90mm, Ø51	43860001*
<i>! ! !</i>	Hand nozzle, soft brush Ø90 mm	43860200*
1	Toothed nozzle width 130 mm, Ø51	43861001**
	Cone nozzle Length 250 mm, Ø51	43862001**
	Scraper nozzle, length: 1000 mm Ø51	43851150**
	Scraper nozzle, length: 500 mm Ø51	43851050**
	Bulk nozzle Length 910 mm, Ø51	43850001*
	Bulk nozzle for floor with handle length 1200 mm, Ø51 mm	43850150**
	Filter candle set, Polypropylene, E+B246fficiency (EN60335-2-69): L	40114180
	Filter candle set, PTFE, Efficiency (EN60335-2-69): M	40114440
	Filter candle set , Antistatic, Efficiency (EN60335-2-69): L	40114190
	Collection bin liner (plastic, 1/ea)	40376934

^{*}ATEX - Suitable for combustible dust with MIE (minimum ignition energy) < 1mJ. Ensure earthing to extraction unit. Not to be used in combustible gas atomspheres or extraction of explosive materials

^{**}ATÉX - Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA , IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials