

Industrial vacuum cleaner 55 S


Dry vacuum cleaner useful in most applications with dust from tools or cleaning operations within industry



The 55S is a efficient three phase compact industrial vacuum cleaner. A very efficient, economical, low noise level and easy to handle dry vacuum. The vacuum is very easy to dismantle and clean. This portable dust collector has long filter lifetime 4-6000 h (with bag filter). The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.

- Long filter lifetime (4-6000 hours)
- Low noise level
- Micro filter as option

Product name	Industrial vacuum cleaner 55 S
Noise level (dB(A))	72
Protection class	IP 55
Filter efficiency (%)	99
Installation	[Indoor]
Material	Casing in sheet metal
Filter cleaning method	[ReverseAirPulse]
Application	[dust], [granulate], [fumes], [swarf]
Working pressure (kPa)	30
Dustbin volume (l)	28
Max Airflow (m3/h)	360
Hose Diameter (mm)	51
Hose length (m)	10
Power Voltage (V)	400
Frequency (Hz)	50
No of phases	3
Filter type	[bag]
Number of filter elements	1
Max vaccum (kPa)	30
Weight (kg)	101
Power (kW)	5,5



Granulate Fumes Swarf Dust










Industrial vacuum cleaner 55 S

[image]	[model]
	40056000*
	40056060**

*Heavy duty cleaning equipment included

**Heavy duty cleaning equipment included. Antistatic filter and micro filter included

Industrial vacuum cleaner 55 S

	[accessory]	[partno]
	Microfilter	40114120
	Hand nozzle, hard brush Ø90mm, Ø51	43860001*
	Hand nozzle, soft brush Ø90 mm	43860200*
	Toothed nozzle width 130 mm, Ø51	43861001**
	Cone nozzle Length 250 mm, Ø51	43862001**
	Scraper nozzle, length: 1000 mm Ø51	43851150**
	Scraper nozzle, length: 500 mm Ø51	43851050**
	Bulk nozzle Length 910 mm	43850001*
	Bulk nozzle for floor length 1200 mm	43850150**

*ATEX: Suitable for combustible dust with MIE (minimum ignition energy) < 1mJ. Ensure earthing to extraction unit. Not to be used in combustible gas atmospheres or extraction of explosive materials

**ATEX: Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA , IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials