

Fan N40



Fan N40

- ✓ Compact
- ✓ Easy to use


A centrifugal fan mainly designed for use with Nederman extraction products.

Note! The fan must not be used in an environment with danger of explosion or for transport of inflammable or explosive gases.





Fan N40

| | |
|---------------------------|--|
| [ProductCertifications] | [ce] |
| [ProductNoiselevel] | 70 at 2500 m3/h |
| [ProductInstallation] | [Indoor], [Outdoor] |
| Material | Fan casings: Sheet metal steel Impeller: Sheet metal steel |
| [ProductAirflow] | 2500 (1,5 kW), 4000 (2,2 kW) |
| Ambient temperature range | -20 to +40 C (-4 F to 104 F) |
| Operating Temperature | Max. 60 C |
| Power voltage (V) | 230/400 |
| Frequency (Hz) | 50 |
| No of phases | 3 |
| Amperage (A) | 8/4,6 |
| Weight (kg) | 29 |
| Power (kW) | 2,2 |

Models

| | Item no |
|---|----------|
|  | 14510123 |

Accessories

| | Accessory | Item no |
|---|---------------------------------------|----------|
|  | FMS 2.5-4 Fan Manual Starter | 14502337 |
|  | FMS 4-6.3 Fan Manual Starter | 14502437 |
|  | Bracket for fan n40 | 14510226 |
|  | Fan onrol Manual 3,2 - 11,5A, 3 fases | 14518737 |

