

Product leaflet

Extraction Arm Telescopic

The arm is flexible in all directions and simple to position and to extend



Nederman

Extraction Arm Telescopic

- The arm has a balanced telescopic action by an adjustable balance block
- The product is suspended by a swivel, which allows the product to rotate 360 degrees
- The product is suspended by a swivel, which allows the product to rotate 360 degrees

The Nederman Telescopic arm is specially designed for working environments with fumes, vapours or non explosive dust, where the space is limited. Typical workplaces can be welding schools or for production in small welding booths, or other industrial processes where a small, easily positioned arm is required. The reach of the arm is between 0.9 and 1.6m (3 and 5 ft).

2025-12-09 2/6

Extraction Arm Telescopic

[ProductCertifications]	[ce]
[ProductStandards]	ISO 21904
[ProductNoiselevel]	76
[ProductInstallation]	[Indoor]
[ProductFumeTemperature]	Max 70° C (158 F)
[ProductExtractionArmdiameter]	160
[ProductAirflow]	1000

Models

	Item no	Arm length (m)	Weight (kg)
-	10502431	0,9 - 1,6	12
	10502331	0,9 - 1,6	12
5	10502531	0,9 - 1,6	12
5	10502731	0,9 - 1,6	12

Accessories

	Accessory	Item no
	Wall bracket for extraction arm	10550635
	Wall bracket extension for fume extractor 2m,3m and 4m arm	10550735
	Wall bracket extension for fume extractor 2m,3m & 4m arm	10550835
	Hood. aluminium. with damper.	10321542
	Hood for telescopic arm	10371086
Example of the second of the s	Transformer 220/24v. 75va.	10361560
	Air flow indicator 500-4500 Pa	10375373
	Air flow indicator 40-600 Pa	10375374
	Spark filter for large metal hood (10321542)	10376329
	Spark filter for round metal hoods, D=249 mm	10373118
Trees.	Transformer 25va. 220-240v. 25va.	10363189
	LED kit for Metal hood (Telescopic extraction arm), including switch, LED, cables, protection net and screws	10376924

