

# Hose Reel 889

Medium sized open hose reel.



This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2025-12-09

1/8

## Hose Reel 889

- ✓ Outlet position can be adjusted through 120° for optimum pull-out and pull-in angle.
- ✓ Spring power can easily be adjusted from the outside.

- ✓ Ratchet easily disengaged when required.

Fitted with slightly larger drums and therefore are able to take longer hoses than Series 888.Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2025-12-09

2/8

Nederman

Hose Reel 889










## Hose Reel 889





[ProductCertifications]	[ce]
[ProductMedia]	Compressed air, Water, Water high pressure, Oil, [adblue]
[ProductConnectionHoseLength]	1
Corrosion resistance	Standard
Electric/Spring driven	Spring

Nederman

Hose Reel 889

Models

	Item no	Media	Delivered with hose	Colour	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
	30800589	Compressed air, Water	[Without]	Black drum / Blue arm	10	1,5	11	20
	30800689	Compressed air, Water	[With]	Black drum / Blue arm	10	1,5	16	
	30800789	Compressed air, Water	[Without]	Black drum / Blue arm	12,5	1,5	11	15
	30800889	Compressed air, Water	[With]	Black drum / Blue arm	12,5	1,5	16	
	30801089	Water	[With]	Black drum / Blue arm	12,5	2	16	
	30801589	Oil	[Without]	Black drum / Blue arm	12,5	7,5	11	15
	30801689	Oil	[With]	Black drum / Blue arm	12,5	7,5	16	
	30801789	Water high pressure	[Without]	Black drum / Blue arm	10	25	11	18
	30801889	Water high pressure	[With]	Black drum / Blue arm	10	25	16	


	Item no	Media	Delivered with hose	Colour	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
	30802489	Oil	[With]	Black drum / Blue arm	12.5	7,5	16	
	30803089 <sup>[1]</sup>	[adblue]	[With]	Black drum / Blue arm	15	1	16	
	30804489	Oil	[With]	Black drum / White arm	12.5	7,5	16	
	30804889	Compressed air, Water	[With]	Black drum / White arm	12.5	1,5	16	

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Nederman

Hose Reel 889

Models














	Item no	Media	Delivered with hose	Colour	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length
	30851089	Compressed air, Water	[With]	Black drum / White arm	10	1,5	16	
	30826889	Compressed air, Water	[With]	Black drum/grey arm	12.5	1,5	16	
	30806789	Oil	[With]	Black drum/grey arm	12.5	7,5	16	
	30806889	Compressed air, Water	[With]	Black drum/grey arm	10	1,5	16	

<sup>[1]</sup> For AdBlue

Hose types

Hose type	[HoseSpecification]	[HoseTemperatureRange]	[HoseFittingDistribution]	[HoseFittingInlet]	[HoseConnectionDistribution]	[HoseConnectionInlet]
B	Cover in NBR/PVC and inner tube in NBR. Synthetic textile braid	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2" + clip
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
M	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive	-30 - 80	Female 60° cone, stainless steel	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone

## Accessories

	Accessory	Item no
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Water gun in chromium plated brass. Max. temperature 95°C	30400110
	Water gun in stainless steel 316. Max. temperature 95°C	30400210
	Watergun EX	30400211
	Water gun in stainless steel 316. Max. temperature 95°C	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810

# Accessories

	Accessory	Item no
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010
	Inlet kit for hose reel 1/2"	30511550
	Inlet kit for hose reel 3/8" with ball valve 3/8", 3/8"-3/8" adapter and 1/4" - 3/8" adapter.	30511650

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2025-12-09

7/8

Nederman

Hose Reel 889

