

Product leaflet

Hose Reel 876

Welding reel designed for maximum safety in oxygen and acetylene welding applications.



Hose Reel 876

- Well ventilated, single layer hose feed and storage highest safety and easy handling without tangles.
- Open design for easy servicing
- Four-way roller guides prevent hose wear.
- Flexible Easy to install on wall, floor or ceiling.
- Compliant with EU directives.

The Hose Reel 876 represents the ultimate solution for oxygen & acetylene or oxygen & LPG welding in terms of safety, durability and easy handling.

Hose Reel 876

Certifications	CE
Connection hose length (m)	1

Models

	Item no	Type of hose	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)
	32827476 ^[1]	К	Oxygen & acetylene	Yes	12	10	10	1,4
•	30831076		Oxygen & acetylene	Yes	15	1x6,3 mm and 1x10 mm	1x6,3 mm and 1x10 mm	2
	30831176		Oxygen & acetylene	Yes	18	6,3	6,3	2
•	30831276		Oxygen & LPG	Yes	15	10	10	2
•	30831376		Oxygen & acetylene	Yes	15	10	10	2
	30831776		Oxygen & acetylene	No				2
1	30831676 ^[2]		Oxygen & acetylene	No				2
	30831876		Oxygen & acetylene, Oxygen & LPG	No				2

^[1] UNF connections [2] With UNF-thread

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
K	Cover and inner tube in rubber, syntethic textile braid (acc. To EN-559)	-20 - 80			Hose nipple + clip	Hose nipple + clip

Accessories

Accessory	Item no
Pivoting bracket.	30372407

2025-12-09 5/6

Nederman

