

Product leaflet

Hose Reel 876

Welding reel designed for maximum safety in oxygen and acetylene welding applications.



Hose Reel 876

- Well ventilated, single layer hose feed and storage highest safety and easy handling without tangles.
- Open design for easy servicing
- Four-way roller guides prevent hose wear.
- Flexible Easy to install on wall, floor or ceiling.
- Compliant with EU directives.

The Hose Reel 876 represents the ultimate solution for oxygen & acetylene or oxygen & LPG welding in terms of safety, durability and easy handling.

Hose Reel 876

Certifications	CE
Connection hose length (ft)	3
Media	Oxygen & acetylene

Models

	ltem no	Type of hose	Delivered with hose	Distribution hose length (ft)	Diameter, connection hose (in)	Distribution hose diameter (in)	Max working pressure (psi)	Weight (lbs)
	32827476 ^[1]	K	Yes	39	3/8	3/8	203	26-30
-	30831676 ^[2]		No				2	

^[1] UNF connections ^[2] With UNF-thread

Hose types

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
K	Cover and inner tube in rubber, synthetic textile braid (acc. To EN-559)	-20 - 80			Hose nipple + clip	Hose nipple + clip

Accessories

	Accessory	Item no
-	Pivoting bracket.	30372407

Nederman

