

Hose Reel 876

Welding reel designed for maximum safety in oxygen and acetylene welding applications.



Hose Reel 876







- ✓ Well ventilated, single layer hose feed and storage - highest safety and easy handling without tangles.
- ✓ Open design for easy servicing
- ✓ Four-way roller guides prevent hose wear.
- ✓ Flexible - Easy to install on wall, floor or ceiling.
- ✓ Compliant with EU directives.

The Hose Reel 876 represents the ultimate solution for oxygen & acetylene or oxygen & LPG welding in terms of safety, durability and easy handling.


Hose Reel 876

Certifications	CE
Connection hose length (m)	1
Max working pressure (Mpa)	2
Corrosion resistance	Standard
Electric/Spring driven	Spring

Models

	Item no	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)
	30831076	Oxygene & Acytylene	Yes	15	1x6,3 mm and 1x10 mm	1x6,3 mm and 1x10 mm
	30831176	Oxygene & Acytylene	Yes	18	6,3	6,3
	30831276	Oxygene & LPG	Yes	15	10	10
	30831376	Oxygene & Acytylene	Yes	15	10	10
	30831776	Oxygene & Acytylene	No			
	30831876	Oxygene & Acytylene, Oxygene & LPG	No			

Accessories

	Accessory	Item no
	Pivoting bracket.	30372407

