

Cable Reel 793

The power cable reel 793 is a robust and comes in 1-phase and 3-phase and is supplied with thermal overload protector.



Cable Reel 793

- ✓ Degree of protection code: IP 55
- ✓ Tested and approved according to IEC 61316
- ✓ Rubber power cable





A heavy duty cable reel for use in industrial environments. The cable reel is available in 1-phase and 3-phase versions and supplied with thermal overload protector.

The Nederman cable reel 793 accommodates power cable lengths up to 25 m (82 ft.). The cable reel components are made of composite materials and galvanized steel.

Cable Reel 793

[ProductCertifications]	[ce]
Electric plug	[without]
Media	[power]
Weight (kg)	15
[ItemDistributionCableType]	H07RN-F
Corrosion resistance	Standard
Electric/Spring driven	Spring

Models

	Item no	Power voltage (V)	No of phases	Amperage (A)	Conductors (No. x mm ²)	Distribution cable length (m)	Power (kW)	[ItemPowerMaxCoiled]
	30700293	230	1	16	3Gx2,5	18	3,7	2.3
	30700493	230	1	16	3Gx2,5	25	3,7	2.3
	30701293	400	3	10	5Gx2,5	15	6,9	5.5
	30701493	400	3	10	5Gx2,5	22	6,9	5.5

