

Product leaflet

Suction hose PE/C



Nederman Suction hose PE/C

Suction hose PE/C

- Smooth bore conductive hose.
- Max. vacuum 50 kPa.
- Temp. range: -40 °C to +60 °C.
- Conductivity < 10^6Ω/m</p>

Application areas: Light and flexible extraction hose. Mainly suited for cleaning and where exceptional conductivity for static electricity is required.

2025-12-09 2/6

Nederman Suction hose PE/C

Suction hose PE/C

Standard Designed for ISO	21904 compliance
---------------------------	------------------

Nederman Suction hose PE/C

Models

Item no	Max vacuum (in. wg)	Diameter (in)	Length (ft)
40160305	7,3	25	49
40160311	7,3	32	16
40160313	7,3	32	33
40160315	7,3	32	49
40160321	7,3	38	16
40160322	7,3	38	33
40160323	7,3	38	49
40160331	7,3	51	16
40160333	7,3	51	49
40160334	7,3	51	33
40160335	7,3	51	98
40160390 ^[1]		38	5
40160400 ^[2]		50	5

Nederman

Models

Item no	Max vacuum (in. wg)	Diameter (in)	Length (ft)
43811001 ^[3]	7,3	38	16
43812103 ^[4]	7,3	51	25
43812200 ^[4]	7,3	51	33
40375955			

^[1] Couplings included (M40 & F40) [2] Couplings included Ø 51 mm [3] Couplings included [4] Couplings included Ø 2 inches

Nederman

Accessories

	Accessory	Item no
	30M Vacuum Hose Storage Hanger - 4.5 in x 3 in (115 mm x 70 mm) for 1.5 in (38 mm) hose up to 16 ft (5 m)	40195450
	60M Vacuum Hose Storage Hanger - 6 in x 4.25 in (150 mm x 110 mm) for 1.5 in (38 mm) hose up to 33 ft (10 m)	40195451
	120M Vacuum Hose Stroage Hanger - 8 in x 6.25 in (200 mm x 160 mm) for 1.5 in (38 mm) hose up to 66 ft (20 m)	40195452
	Floor Tool, Hose and Accessories Metal Wall Storage Rack - 21 in x 20 in x 12 in (542 mm x 490 mm x 305 mm)	40196370
0	Hose clamp 85	40903030
0	Hose clamp 56	40903170
0	Hose clamp 75	40903180
0	Hose clamp 112	40903210
6	Hose clamp 104-112 ABA Robust	40903270
	End sleeve PE d38 antistatic w/male	43819012
	End sleeve PE d38 antistatic w/fema	43819013