

# Suction hose PE



## Suction hose PE













- ✓ Temp. range: -40° to +60 °C.
- ✓ Max. vacuum 50 kPa.

Application areas: Single suction hose, mainly intended for simple cleaning. The hose is not conductive.


# Suction hose PE

Standard	Designed for ISO 21904 compliance
----------	-----------------------------------












## Models

	Item no	Max vacuum (kPa)	Diameter (mm)	length (m)
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160743	50	51	10
	40160745	50	51	20
	43812300			
	43812400			

Models

	Item no	Max vacuum (kPa)	Diameter (mm)	length (m)
	43812500			

## Accessories

	Accessory	Item no
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	End sleeve PE d32	43819001
	End sleeve d38, pe	43819011