

Sugeslange PE



Sugeslange PE

- ✓ Temp.område: -40° til +60 °C.
- ✓ Maks. vakuum 50 kPa.

Bruksområder: Enkel avsugsslange, beregnet for enkel rengjøring. Slangen er ikke ledende.

Sugeslange PE

Standard	Designed for ISO 21904 compliance
----------	-----------------------------------

Models

	Item number	[ItemMaxVaccum]	Diameter (mm)	[ItemLength]
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160743	50	51	10
	40160745	50	51	20
	43812300			
	43812400			

Models

	Item number	[ItemMaxVaccum]	Diameter (mm)	[ItemLength]
	43812500			

Accessories

	Accessory	Item number
	Slangehylle 30 m 115x70	40195450
	Slangehylle 60 m 150x110	40195451
	Slangehylle 120 m 200x160	40195452
	Slange og ekst. hylle	40196370
	Slangeklemme 85	40903030
	Slangeklemme 56	40903170
	Slangeklemme 75	40903180
	Slangeklemme 112	40903210
	Slangeklemme 104-112 ABA Robust	40903270
	Endehylse PE d32	43819001
	Endehylse d38,pe	43819011