

Sugslang PE



Sugslang PE

- ✓ Temp. område: -40 till +60 °C.
- ✓ Max. vakuum: 50 kPa.

Användningsområde: Enkel sugslang, som främst är avsedd för enklare städning. Slangen är ej ledande.

Sugslang PE

Standarder	Designed for ISO 21904 compliance
------------	-----------------------------------

Modeller

	Art.nr	Max vaccum (kPa)	Diameter (mm)	Längd (m)
	40160712	50	25	10
	40160722	50	32	10
	40160731	50	38	5
	40160733	50	38	10
	40160735	50	38	20
	40160741	50	51	5
	40375953	50	32	5
	40160370		38	5
	40160380		50	5
	40160743	50	51	10
	40160745	50	51	20
	43812300			
	43812400			

Modeller

	Art.nr	Max vaccum (kPa)	Diameter (mm)	Längd (m)
	43812500			

Tillbehör

	Tillbehör	Art.nr
	Slanghylla 30 m 115x70	40195450
	Slanghylla 60 m 150x110	40195451
	Slanghylla 120 m 200x160	40195452
	Slang & Tillbehörshylla	40196370
	Slangklämma 85	40903030
	Slangklämma 56	40903170
	Slangklämma 75	40903180
	Slangklämma 112	40903210
	Slangklämma ABA Robust 104-112	40903270
	Ändhylsa PE d32	43819001
	Ändhylsa d38, pe	43819011