

Suction hose FS



Suction hose FS

- ✓ Temp. range: 0 to +80 °C.
- ✓ Max. vacuum 60 kPa.

Application areas: Flexible hose with steel helix to discharge static electricity. Mainly used for extraction from handtools and balance arms.

Suction hose FS

Certifications	CE
Standard	Designed for ISO 21904 compliance

Models

	Item no	Max vacuum (in. wg)	Diameter (in)	Length (ft)
	40160102	8,7	25	49
	40160152	8,7	32	49
	40160202	8,7	38	49
	40160223	8,7	44	49
	40160252	8,7	51	49
	40160263	8,7	63	49
	40160350			
	40160360			

Accessories

	Accessory	Item no
	30M Vacuum Hose Storage Hanger - 4.5 in x 3 in (115 mm x 70 mm) for 1.5 in (38 mm) hose up to 16 ft (5 m)	40195450
	60M Vacuum Hose Storage Hanger - 6 in x 4.25 in (150 mm x 110 mm) for 1.5 in (38 mm) hose up to 33 ft (10 m)	40195451
	120M Vacuum Hose Storage Hanger - 8 in x 6.25 in (200 mm x 160 mm) for 1.5 in (38 mm) hose up to 66 ft (20 m)	40195452
	Floor Tool, Hose and Accessories Metal Wall Storage Rack - 21 in x 20 in x 12 in (542 mm x 490 mm x 305 mm)	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	PVC-EPDM Ball Valve Type 353 with (2) hose clamps for vacuum hoses - D = 1.5 in (38 mm)	40615210
	Ball valve Ø44 mm PVC compl.	40376978