

Product leaflet

# Suction hose PVC



**Nederman** Suction hose PVC

## Suction hose PVC



Temp. range: -20° to +70 °C.

Application areas: Robust oil-resistanthose, smooth inside. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease. Technical data:

**Nederman** Suction hose PVC

## Suction hose PVC

Standard	Designed for ISO 21904 compliance
----------	-----------------------------------

Nederman



#### Models

Item no	Max vacuum (in. wg)	Diameter (in)	Length (ft)
43822200 <sup>[1]</sup>	12,2	51	33
43822300 <sup>[2]</sup>	12,2	51	82
43822301 <sup>[1]</sup>		51	25
43822600 <sup>[1]</sup>	12,2	51	25

 $<sup>^{[1]}</sup>$  Couplings included, Ø 51 mm  $^{[2]}$  Without couplers

**Nederman** Suction hose PVC

### Accessories

	Accessory	Item no
	30M Vacuum Hose Storage Hanger - 4.5 in x 3 in (115 mm x 70 mm) for 1.5 in (38 mm) hose up to 16 ft (5 m)	40195450
	$60$ M Vacuum Hose Storage Hanger - $6$ in $\times$ $4.25$ in ( $150$ mm $\times$ $110$ mm) for $1.5$ in ( $38$ mm) hose up to $33$ ft ( $10$ m)	40195451
	$120$ M Vacuum Hose Stroage Hanger - $8$ in $\times$ $6.25$ in ( $200$ mm $\times$ $160$ mm) for $1.5$ in ( $38$ mm) hose up to $66$ ft ( $20$ m)	40195452
	Floor Tool, Hose and Accessories Metal Wall Storage Rack - 21 in x 20 in x 12 in (542 mm x 490 mm x 305 mm)	40196370
0	Hose clamp 56	40903170
0	Hose clamp 75	40903180
0	Hose clamp 85	40903030
0	Hose clamp 112	40903210
6	Hose clamp 104-112 ABA Robust	40903270

2025-12-09 5/5