

ALU 150/250

Ett avancerat avgasutsugsystem för fordon i rörelse



ALU 150/250

- ✓ Högkvalitativa komponenter
- ✓ Två standardskenstorlekar
- ✓ Komplet program av tillbehör till utsugsenheter
- ✓ Large airflow

ALU 150/250 är ett avancerat avgasskensystem för hög användningsfrekvens. ALU 150/250 erbjuder ett stort antal funktioner, manuell återgång av sugenheter, automatisk frångkoppling av munstycken. OBS! När du använder en rak skenlösning måste en hydraulisk ändstopp (se tillbehör) fästas i slutet av skensystemet.

ALU 150/250

Cerifikat	CE
-----------	----

Modeller

	Art.nr	Slangtyp	Diameter, slang (mm)	Slanglängd (m)
	20900510 ^[1]			
	20900610 ^[1]			
	20900710 ^[1]			
	20900810 ^[1]			
	20900910 ^[1]			
	20901010 ^[1]			
	20901110 ^[1]			
	20901210 ^[1]			
	20901310 ^[1]			
	20901410 ^[1]			
	20901510 ^[1]			
	20901610 ^[1]			
	20901710 ^[1]			

Modeller

	Art.nr	Slangtyp	Diameter, slang (mm)	Slanglängd (m)
	20901810 ^[1]			
	20901910 ^[1]			
	20902010 ^[1]			
	20950010 ^[2]			
	20950110 ^[3]			
	20950210 ^[4]			
	20950310 ^[5]			
	20950410 ^[6]			
	20950510 ^[7]			
	20950610 ^[8]			
	20950710 ^[9]			
	20950810 ^[10]			
	20950910 ^[11]			

Modeller

	Art.nr	Slangtyp	Diameter, slang (mm)	Slanglängd (m)
	20951010 ^[12]			
	20951110 ^[13]			
	20951210 ^[14]			
	20951310 ^[15]			
	20951410 ^[16]			
	20951510 ^[17]			
	20900310 ^[18]	NR-CP	100	5
	20900410 ^[18]	NR-CP	150	5
	20902610 ^[18]	NR-CP	150	7,5
	20902710 ^[18]	NR-CP	150	7,5

^[1] Rak avgasskena ALU 150 inkl. upphängningsbeslag. För längder > 50 m, vänligen kontakta din Nederman-återförsäljare.

^[2] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 2 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 2,5m, fasteners for rail assembly.

^[3] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 2 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 5m, fasteners for rail assembly.

^[4] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 3 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 7,5m, kit connections and fasteners for rail assembly.

^[5] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 3 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 10m, kit connections and fasteners for rail assembly.

^[6] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 4 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 12,5m, kit connections and fasteners for rail assembly.

^[7] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 4 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 15m, kit connections and fasteners for rail assembly.

^[8] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 5 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 17,5m, kit connections and fasteners for rail assembly.

^[9] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 5 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 20m, kit connections and fasteners for rail assembly.

^[10] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 6 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 22,5m, kit connections and fasteners for rail assembly.

^[11] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 6 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 25m, kit connections and fasteners for rail assembly.

^[12] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 7 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 27,5m, kit connections and fasteners for rail assembly.

^[13] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 7 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 30m, kit connections and fasteners for rail assembly.

^[14] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 8 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 35m, kit connections and fasteners for rail assembly.

^[15] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 9 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 40m, kit connections and fasteners for rail assembly.

^[16] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 10 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 45m, kit connections and fasteners for rail assembly.

^[17] Straight exhaust rail ALU 250 incl. suspension brackets. Ceiling Support 11 pcs., lid 2 pcs., end stop 2 pcs., rubber moulding 50m, kit connections and fasteners for rail assembly.

^[18] Levereras med vagn, balansblock, utsugsslang och munstycke. Slangtyp NR-CP.

Tillbehör

	Tillbehör	Art.nr
	Avkopplingskena ALU 150/250	20940810
	Hydraulisk Dämpare ALU150/250	20941410
	Konsol för upphängningsdon 5 st	20940110
	Upphängningskonsol vägg 600 mm	20947510
	Stag för ALU150/250 10 st	20941110
	Skenförstärkning	20373942
	Sugvagn Maxi	20940310
	Sugvagn för rökätare	20940210
	Hållare för balansblock Stdvagn	20941310
	Konsol balansblock rökätare	20941210
	Sugvagn ALU150 Ø150 std	20943210
	Sugvagn ALU150 Ø150 std med spjäll	20943410
	Sugvagn Reel on Rail	20948610

Tillbehör

	Tillbehör	Art.nr
	Ändanslutning ALU 150 med slang	20816264
	Extractor side ALU 250 Ø250 with hose	20377374
	Kit connection ALU 250	20377371
	Extractor top side Ø250 with hose	20377373
	Extractor top Ø250 W/hose	20377372
	Skarvprofil ALU150 sats	20373413
	Ceiling Support bracket 5pcs, ALU250	20377370

Y= Pressure drop (Pa), X= air flow (m³/h) A = ALU Ø150 mm B = ALU Ø250 mm

Pressure drop extraction units with A= hose Ø 100 mm, 5 m B= hose Ø 150 mm, 7.5 m C= hose Ø 150 mm, 5 m

Y= Pressure drop (Pa), X= air flow (m³/h) A = Trolley fume extractor arm B = Top Outlet - side Ø250 C = Maxi Trolley Ø200 without hose D = Rail end outlet ALU 250 / Ø250 E = Top outlet Ø250 F = Rail end outlet ALU 150 / Ø250