

RBU

When extra suction is needed when larger and heavier pieces need to be taken care of or need to be transported through long pipelines.



RBU

- ✓ Powerful units with V-belt Root's pump
- ✓ Different model versions
- ✓ Equipped with acoustic enclosure
- ✓ Used when extra extraction power is needed

Nederman RBU units work uninterruptedly with strong suction and a maintained efficiency. This is the perfect vacuum source in larger systems where powerful vacuum is required to balance for large pressure drop in long pipes or hoses. As standard supplied with vacuum and discharge silencers, universal valve including vacuum regulator, safety valve and back flush valve. Applications: cleaning, swarf removal, grinding, sanding, welding. Also in installations where extra extraction power is needed, e.g. heavy material or long piping system.

RBU



Certifications	CE
Standard	Designed for ISO 21904 compliance
Installation	Outdoor, Indoor
Power voltage (V)	400
Frequency (Hz)	50
No of phases	3
Noise level (dB(A))	70

Models

	Item no	Capacity (max airflow m3/h)	Max vacuum (kPa)	Power (kW)
0	40103702 ^[1]	1600	33	22
1	40103713 ^[1]	2000	33	30
2	40103723 ^[1]	2000	45	37
3	40103732 ^[1]	2600	33	37
4	40103742 ^[1]	2600	45	45
5	40103753 ^[1]	3200	45	55

^[1] Motor type - IE3

Accessories

	Accessory	Item no
	Silencer LT200	40139100
	Bend spiro BU 200mm 90dgr	40132540

