

Product leaflet

112A

Removal of grease and high viscosity material



112A

- ✓ Comes with NE 74 powerhead
- ✓ Wet cleaning
- ✓ Vacuuming capacity
- ✓ Easy handling

A high capacity vacuum unit for suction and transportation of grease and other high viscosity material. The material is collected in a plastic bag for easier discharge. Suction equipment is made for heavy duty work. The container is mounted to the trolley by brackets.

112A

Sertifiseringer	CE
Filtertype	Stavfilter
Antall filterelementer	1
Filtermateriale	Polyester-teflon
[ItemCompressedAirRequirement]	5,3 Nm ³ /min
[ItemMaxAirFlow]	318
[ItemNoiselevel]	75.0
[ItemMaxVaccum]	-78

Models

	Item number	Slangetype	[ItemHVBHoseLength]	[ItemHVBHoseDiameter]
	42111202 ^[1]	PVC	7,5	51
	42111203 ^[1]	PU12	5	38

^[1] Med børste og konisk munnstykke

Hose types

Slangetype	Spesifikasjon	Temperaturområde (°C)	Endekobling, distribusjonsslange	Endekobling, innløpsslange	Slangetilkobling på trommel, distribusjonsslange	Slangetilkobling på trommel, innløpsslange
PVC	Maks vakuum -84kPa. Indre bøyeradius 60mm. Forsterket med innstøpt stålspiral.	- 20 deg. C. to + 70 Deg. C.				
PU12	Solid slange. Velegnet for slitende materialer. Transparent polyurethan 1,2mm. Forsterket med innstøpt stålspiral.	- 40 deg. C. - + 90 Deg. C.				

Accessories

	Accessory	Item number
	Kontroll Sfor NE86-96	43222008
	Kontroll Sfor NE 22-76	43220026
	Kontroll Sfor NE 22-76	43220001

Air Powered ejectors All performance data are based on 7 bar supply pressure