

112A

Removal of grease and high viscosity material



112A

- ✓ Comes with NE 74 powerhead
- ✓ Wet cleaning
- ✓ Vacuuming capacity
- ✓ Easy handling

A high capacity vacuum unit for suction and transportation of grease and other high viscosity material. The material is collected in a plastic bag for easier discharge. Suction equipment is made for heavy duty work. The container is mounted to the trolley by brackets.

112A

Cerifikat	CE
Typ av filter	Påsfilter
Antal filter	1
Filtermaterial	Polyester-teflon
Tryckluftsbekov	5,3 Nm ³ /min
Max luftflöde (m ³ /h)	318
Ljudnivå (dB(A))	75.0
Max vaccum (kPa)	-78

Modeller




Art.nr	Slangtyp	Slanglängd (m)	Slangdimension (mm)
42111202 ^[1]	PVC	7,5	51
42111203 ^[1]	PU12	5	38

^[1] Med borste och koniskt munstycke.

Slangtyper

Slangtyp	Specifikation	Temperatur område, °C	Slangkoppling, fri ände distributionsslang	Slangkoppling, fri ände anslutningsslang	Slanganslutning på upprullare, distributionsslang	Slangkoppling på upprullare, anslutningsslang
PVC	Max vacuum 84 kPA Inre krökningsradie 60 mm Förstärkt med helinbäddad stålspiral	- 20 deg. C. to + 70 Deg. C.				
PU12	Lämplig för slitande material Transparent polyuretanslang Förstärkt med helinbäddad stålspiral	- 40 deg. C. -+ 90 Deg. C.				

Tillbehör

	Tillbehör	Art.nr
	Kontrollsystem för NE86-96 utan kontrollbox	43222008
	Kontrollsystem för NE 22-76, utan kontrolbox	43220026
	Kontrollsystem för ejektor NE 22-76	43220001

Air Powered ejectors All performance data are based on 7 bar supply pressure