

Product leaflet

# 425A

Industrial vacuum cleaner for removal of industrial waste



## 425A


- ✓ Dry waste suction
- ✓ Silo pre-separator with manual outlet valve
- ✓ Fork lift handling
- ✓ Sturdy trolley system with large wheels for uneven ground
- ✓ automatic filtercleaning

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

## 425A

Sertifiseringer	CE
Filtertype	Kassettfilter
Antall filterelementer	1
Slangetype	PVC
[ItemCompressedAirRequirement]	3,0 Nm <sup>3</sup> /min
[ItemMaxAirFlow]	342
[ItemNoiselevel]	75,5
[ItemMaxVaccum]	-52
Vekt (kg)	119
[ItemHVBHoseLength]	7,5
[ItemHVBHoseDiameter]	51



## Models


	Item number
	42142500

## Hose types

Slangetype	Spesifikasjon	Temperaturområde (°C)	Endekobling, distribusjonsslange	Endekobling, innløpsslange	Slangetilkobling på trommel, distribusjonsslange	Slangetilkobling på trommel, innløpsslange
PVC	Maks vakuum -84kPa. Indre bøyeradius 60mm. Forsterket med innstøpt stålspiral.	- 20 deg. C. to + 70 Deg. C.				

# Accessories

	Accessory	Item number
	Kontroll Sfor NE86-96	43222008
	Kontroll Sfor NE 22-76	43220026
	Kontroll Sfor NE 22-76	43220001



Air Powered ejectors All performance data are based on 7 bar supply pressure