

410E

Industrial vacuum cleaner for removal of industrial waste materials



410E

- ✓ Dry waste suction
- ✓ Silo pre-separator with manual outlet valve
- ✓ Fork lift handling
- ✓ Sturdy trolley system with large wheels for uneven ground

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container for the removal of industrial waste materials. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple. The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The model include slots for handling by forklift.

410E

Cerifikat	CE
Installation	Inomhus
Metod för filterrensning	Mekaniskt
Applikation	Stoft, Rök, Spån, Granulat
Matningsspänning (V)	230
Frekvens (Hz)	50
Faser	1
Typ av filter	Patron
Antal filter	1
Filtermaterial	Papper
Uttagstyp	Euro (CEE 7/2 P+E)
Slangtyp	PE/C
Max luftflöde (m³/h)	460
Ljudnivå (dB(A))	75
Max vaccum (kPa)	-21,5
Slanglängd (m)	7,5
Slangdimension (mm)	51
Effekt (kW)	2,4

Modeller

	Art.nr
	42441000 ^[1]

^[1] Med städset, skrap- och koniskt munstycke

Slangtyper

Slangtyp	Specifikation	Temperatur område, °C	Slangkoppling, fri ände distributionsslang	Slangkoppling, fri ände anslutningsslang	Slanganslutning på upprullare, distributionsslang	Slangkoppling på upprullare, anslutningsslang
PEC	För städning Max vacuum 50 kPa Ledningsförmåga < 10 ⁶ Ohm	-40°C - +60°C				