

Product leaflet


# MagnaRail Green

High quality low maintenance exhaust removal system.



#### MagnaRail Green





MagnaRail Green is a high capacity system designed to handle high operation requirements. Up to two vehicles can be attached to the same rail for a drive through or back in application for vehicles with low level tail pipes. The suction rail is formed in a configuration such that the extrusion serves not only as an exhaust duct, but also as the guide rail that the extraction trolley travels in. The rail is available up to 99 ft.

The fan/duct work can be connected to the rail via either an end outlet or one/several top outlets depending on the length of the rail.

6" diameter hose - The system uses a 6" diameter hose providing up to 800 cfm, the most of any system on the market.

8" Nozzle - The 8" diameter nozzle provides greater ambient air intake providing cooling air which extends system life.

Anchor Plate - The Nederman system attaches to an anchor plate mounted on the vehicle body and uses that for the pulling force of the system, not the exhaust pipe which was never designed to pulled on by systems that attach to the exhaust pipe.

Specialty Nozzles - Nederman designs special nozzles to work with and fit the newer EPA 07 tailpipes. We do not need to change the tip of the exhaust pipe to work with the Green system which could void the manufacturer's warranty.

Auto Start System - With the Nederman Auto Start System, the exhaust fan is activated prior to the start of the vehicle's engine ensuring 100% capture of exhaust. Other styles of starting systems are unreliable and prone to failure.

MagnaRail Green

2025-12-09 3/7

#### Models

Item no	Diameter, hose (mm)	Hose length (m)
20817064 <sup>[1]</sup>	160	3
20816964 <sup>[1]</sup>	160	4

<sup>[1]</sup> Including - Aluminum track (1), Mounting brackets for 2.4 m distance (2), Rubber stop (3), Sliding block (4), Balancer (5), Swivel (6), Hose connector, Exhaust hose (7), Low level nozzle, length - 0,6 m, diameter - 130 mm (8), Electro-magnet assembly (9), Anchor plate (10)

2025-12-09 4/7

Nederman

## Accessories


	Accessory	Item no
	Exhaust rail 920 L= 17.5 M (57')	20916620
	Exhaust rail 920 L= 7.5 M (25′)	20916220
	Exhaust rail 920 L= 10.0 M (33′)	20916320
	Exhaust rail 920 L= 12.5 M (41')	20916420
	Exhaust rail 920 L = 15.0 M (50′)	20916520
	Exhaust rail 920 L= 20.0 M (66′)	20916720
	Exhaust rail 920 L= 22.5 M (74′)	20916820
	Exhaust rail 920 L= 25.0M (82′)	20916920
	Exhaust rail 920 L = 27.5 M (90´)	20917020
	Exhaust rail 920 L= 30.0M (99´)	20917120
J	MagnaSystem Nozzle STD	20802164
J	MagnaSystem Nozzle HB 600	20802264
J	MagnaSystem Nozzle HB 900	20802464

### Accessories

	Accessory	Item no
	Anchor plate for magnatrack.	20372003
	Top outlet Ø200 for 920	20374246
	Radio transmitter vehicle GHz	20376723
	Radio Receiver GHz	20376724
	Handheld radio transmitter GHz	20376725
	Hose protection ø130/160 (Pair)	20374428
-	Twist support, HL nozzle	20374364
Ĭ	Lengthening shaft, HL nozzle	20374359

2025-12-09 6/7

Nederman



A: Pressure drop, Pa B: Airflow, m3/h C: Airflow cfm D: Pressure drop, in w.g. Top diagram: 1 = Top connection angled, Ø 200 mm 2 = End connection 3 = Exhaust rail, per metre Bottom diagram 1 = Extraction unit LL, hose 4 m, Ø130 mm 2 = Extraction unit LL, hose 4 m, Ø160 mm 3 = Extraction unit HL, hose 2 m, Ø160 mm Airflow recommendations: Heavy vehicles: 1000 - 1200 m3/h Car / SUV: 400 - 600 m3/h