

Product leaflet

# Exhaust Hose NFC-2

High temperature hose



## Exhaust Hose NFC-2








- ✓ Specifically designed to be flexible and ductile, and to have a very low pressure drop. They are resistant to all chemicals in diesel and petrol exhaust fumes, and show high resistance to mechanical stress.
- ✓ Temperature range: Continuous use: +150 °C Short-term use: +200 °C
- ✓ Temperature range: Continuous use: +150 °C Short-term use: +200 °C

Specifically designed to be flexible and ductile, and to have a very low pressure drop. They are resistant to all chemicals in diesel and petrol exhaust fumes, and show high resistance to mechanical stress.














# Exhaust Hose NFC-2

Certifications	CE
----------------	----














Models

	Item no	Type of hose	Diameter, hose (in)	Hose length (ft)
	20825862	NFC-2	3	16
	20825962	NFC-2	4	16
	20826062	NFC-2	4	25
	20826162	NFC-2	5	16
	20826262	NFC-2	5	25
	20826362	NFC-2	6	16
	20826462	NFC-2	6	25








## Accessories

	Accessory	Item no
	Hose suspension Diameter = 3 in (75 mm)	20373615
	Hose suspension Diameter = 4 in (100 mm)	20373607
	Hose suspension Diameter = 6 in (150 mm)	20373609
	Hose suspension Diameter = 5 in (125 mm)	20373608
	Exhaust Nozzle Quick Coupling for hose Diameter = 4 in (100 mm) - Qty 2 pcs	20374641
	Connection kit 4" for quick coupler	20375048
	Mechanical quick coupler 4", male	20375049
	Safety Coupling 6" male	20376017
	Y-pipe Ø100 (4 in)/100 (4 in)/100 (4 in)	20376647
	Galv. Steel Hose Coupling Kit - 4 in (100mm) ID with (2) sleeves and (1) strap	20947410
	Galv. Steel Hose Coupling Kit - 5 in (125 mm) ID with (2) sleeves and (1) strap	20948710
	Galv. Steel Hose Coupling Kit - 6 in (150 mm) ID with (2) sleeves and (1) strap	20948810
	Rubber cover with hose clip, Diameter = 8 in (200 mm) - Pair	20373838

## Accessories

	Accessory	Item no
	Quick coupling D=100 (4") male	20947710
	Quick coupling D=100 (4") female	20948110
	Female Quick Hose Coupling for NFC and NR-CP Hoses - Diameter = 6 in (150 mm)	20948310
	Male Quick Hose Coupling for NFC and NR-CP Hoses - Diameter = 6 in (150 mm)	20947910
	Connection set 3"	20373286
	Connection set 4"	20373287
	Connection set 5"	20373288
	Connection set 6"	20373289
	Exhaust Hose 90° Lifting Elbow with eyelet for balancer cable - Diameter = 102 mm (4 in )	20344591
	Exhaust Hose 90° Lifting Elbow with eyelet for balancer cable - Diameter = 127 mm (5 in )	20344592
	Exhaust Hose 90° Lifting Elbow with eyelet for balancer cable - Diameter = 152 mm (6 in )	20344593
	Hose suspension DN 100 (4 in) - 150 (6 in)	20374530
	Adapter for vehicle Exhaust Hose Diameter = 3 in (75 mm) - Includes 4 to 3 in adapter, 3 in (75 mm) rubber sleeve and hose clamp	20373128

## Accessories

	Accessory	Item no
	Exhaust Hose Safety Quick Coupling (male and female) with (2) sleeves and (2) hose clamps - PU UV - Diameter = 4 in (100 mm)	20374541
	Safety coupling 6"	20374543
	Connector Diameter = 6 in (150mm) - Diameter = 5 in (125 mm) - Steel	20344353
	Connector 5"-4". steel.	20344354
	Connector 4"-3". steel.	20342483
	Junction pipe d=160 (6.25 in)	20371413
	Exhaust Hose 90° Lifting Elbow with eyelet for balancer cable - Diameter = 200 mm (8 in)	20371927