

Streamline Modul Kabinett

Et modulært kabinettssystem for effektiv oppsamling og
oppfanging av sveiserøyk



Streamline Modul Kabinett

- ✓ Effektiv og sikker: utløpsdesign med ledeplate for optimal luftstrøm, mindre luftvolum og gnistavskrekkende effekt
- ✓ Ergonomisk: med gjennomsiktig polykarbonattak for forbedret sikt uten ekstra belysning
- ✓ Rask og plassbesparende: rask og enkel montering, med lavprofildesign og lett konstruksjon som gjør at den kan installeres hvor som helst, noe som minimerer behovet for forsterkninger i gulv eller tak.
- ✓ Allsidig: modulær konstruksjon med et bredt utvalg av størrelser, fra 1,5 x 1,5 m og med størrelsesintervaller på 0,5 m, for å passe til ulike celle- og sveiseområdedimensjoner.
- ✓ Fleksibel: flere installasjonsalternativer med justerbar høyde, utløpsposisjon og kanaltilkoblingsstørrelse.

Streamline Modul system er en fleksibel og høytytende innkapsling som er utformet for å beholde og kontrollere støv, røyk og gnister som genereres under robot- eller manuelle sveiseprosesser. Ved å forhindre spredning av forurensninger i hele anlegget forbedrer Streamline-systemet arbeidernes helse og sikkerhet, samtidig som den reduserer vedlikeholds- og rengjøringskostnader. Den lokaliserte inkapslingsmetoden er både mer økonomisk og energieffektiv sammenlignet med konvensjonelle hetter eller systemer for rensing av omgivelsesluft, noe som reduserer det totale nødvendige luftvolumet betydelig.

Streamline Modul Kabinett

Installasjon	Innendørs
[ProductTechnicalData]	Ramme med uttak (1, 2 eller 3 uttak avhengig av rammens størrelse), med et 0,4 mm tykt sveiseforheng og mulighet for plassering eller oppheng.
[ProductDimension]	Rammer tilgjengelig i dimensjoner fra 1,5 x 1,5 til 6 x 3 m (størrelsene øker med 0,5 m i lengderetningen og bredden). Rammemontering på ben opptil 3 m høye og på forsterkede ben opptil 6 m. Hengende montering mulig.

Models

	Item number	Vekt (kg)	[ItemCapacityAux]
	73009911 ^[1]	75 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 2700 m3/t
	73009912 ^[2]	72 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 3300 m3/t
	73009913 ^[2]	89 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 3300 m3/t
	73009914 ^[2]	88 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 4200 m3/t
	73009915 ^[3]	105 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 4200 m3/t
	73009950 ^[3]		Maks luftmengde 4200 m3/t
	73009916 ^[3]	101 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 4200 m3/t
	73009917 ^[3]	110 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 4200 m3/t
	73009918 ^[4]	113 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5200 m3/t
	73009919 ^[4]	130 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5200 m3/t
	73009920 ^[5]	116 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5400 m3/t
	73009921 ^[4]	116 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5200 m3/t
	73009922 ^[4]	124 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5200 m3/t

Models

	Item number	Vekt (kg)	[ItemCapacityAux]
	73009923 ^[4]	140 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5200 m3/t
	73009924 ^[5]	144 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5400 m3/t
	73009925 ^[5]	154 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5400 m3/t
	73009926 ^[6]	165 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6800 m3/t
	73009927 ^[6]	175 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6800 m3/t
	73009928 ^[5]	148 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 5400 m3/t
	73009929 ^[7]	158 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009930 ^[6]	169 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6800 m3/t
	73009931 ^[6]	179 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6800 m3/t
	73009932 ^[8]	152 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009933 ^[8]	179 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009934 ^[8]	181 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009935 ^[6]	193 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6800 m3/t

Models

	Item number	Vekt (kg)	[ItemCapacityAux]
	73009936 ^[8]	166 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009937 ^[8]	179 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 6600 m3/t
	73009938 ^[9]	185 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 8400 m3/t
	73009939 ^[10]	230 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 8600 m3/t
	73009940 ^[11]	170 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 8100 m3/t
	73009941 ^[11]	184 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 8100 m3/t
	73009942 ^[9]	197 (weight of frame, polycarbonate and outlet, excl. weight of curtain and legs)	Maks luftmengde 8400 m3/t
	73009943 ^[12]		Maks luftmengde 8400 m3/t

^[1] 1 utløp ø250 mm

^[2] 1 utløp ø280 mm

^[3] 1 utløp ø315 mm

^[4] 1 utløp ø350 mm

^[5] 2 utløp ø250 mm

^[6] 1 utløp ø400 mm

^[7] 3 utløp ø280 mm

^[8] 2 utløp ø280 mm

^[9] 2 utløp ø315 mm

^[10] 1 utløp ø450 mm

^[11] 3 utløp ø250 mm

^[12] 2 utløp ø315 mm. Eks. gardin.

Accessories

	Accessory	Item number
	SET Support Post x4	73009944
	SET Support Post x6	73009945
	SET Support Post x8	73009946
	Inlet galv. For Fan Dia. 250/250 Spiro	73003454
	Inlet galv. for fan dia 280 / spiro 280	73001375
	Inlet galv. for fan dia 315 / spiro 315	73003457
	Inlet galv. For Fan Dia. 350/350 Spiro	73001260
	Inlet galv. for fan dia 400 / spiro 400	73003465
	Inlet galv. for fan dia. 450/450 Spiro	73007729
	Inlet galv. for fan dia 250 / spiro 200	73003451
	Inlet galv. for fan dia 250 /Spiro224	73007122
	Inlet galv. for fan dia 280 /Spiro224	73007128
	Inlet galv. for fan dia 280 /Spiro250	73007129

Accessories

	Accessory	Item number
	Inlet galv. for fan dia 315 /Spiro250	73007137
	Inlet galv. for fan dia 315 /Spiro280	73007138
	Inlet galv. for fan dia 355 /Spiro280	73007144
	Inlet galv. for fan dia 355 / spiro 315	73003458
	Inlet galv. For Fan Dia. 355/350 Spiro	73003461
	Inlet galv. for fan dia 400 /Spiro315	73007150
	Inlet galv. for fan dia 400/ Spiro 355	73007153
	Inlet galv. for fan dia 450/ Spiro 355	73007159
	Inlet galv. for fan dia 450 / spiro 400	73003466
	Gnistfanger Galvanisert 0,7mm 250QF	8210001268
	Gnistfanger Galvanisert 0,7mm 315QF	8210001269
	Gnistfanger Galvanisert 0,7mm 400QF	8210001270
	Gnistfanger Galvanisert 0,9mm 450QF	8210001271

Accessories

	Accessory	Item number
	Weld Curtain PVC Red 1,4mx25m (full roll)	7946869
	Weld Curtain PVC Red 1,4mx50m (full roll)	7946555
	SET support Post x6 - 6m	73009957
	SET Support post x8 - 6m	73009958