

Hose Reel 883

Retractable hose reel suitable for vehicle repair shops, garages and maintenance workshops.



Este contenido está protegido por la ley de derechos de autor, se proporciona únicamente con fines informativos y está sujeto a cambios sin previo aviso. © Nederman Holding AB

2025-12-04

1/7

Nederman

Hose Reel 883

Hose Reel 883

- ✓ Spring tension easily adjustable from the outside
- ✓ Fast and easy to service
- ✓ Simple hose replacement without dismantling the reel

A fully plate encased and robust, medium sized retractable hose reel. A highly suitable hose reel for applications in vehicle repair and maintenance workshops. The retractable hose reel is supplied with loose quick hitch for easy installation. The hose reel 883 is retractable and has an optimized spring force, ensuring that the hose retracts smoothly and evenly onto the drum. The high quality spring is pre-tensioned at the factory to suit a wide range of applications, and is well protected inside the drum cavity. The self retracting hose reel 883 is very easy to mount, either on walls, ceilings or floors.

Hose Reel 883

Certificaciones	[ce]
[ProductMedia]	Aire comprimido, Agua, Agua a alta presión, Aceite, Grasa
Tipo de manguera	[B]
Medios	Aire comprimido, Agua
Se entrega con manguera	Con
Presión máxima de trabajo (Mpa)	1,5
Peso (kg)	15
[ItemCorrosionResistance]	[Standard]
[ItemElectricSpringDriven]	Resorte

Nederman

Hose Reel 883

Modelos

	No. De Artículo	Longitud de la manguera de distribución (m)	Diámetro de la manguera de conexión (mm)	Diámetro de la manguera de distribución (mm)
	32850883 ^[1]	15	12.5	10
	32851083 ^[2]	10		12.5

^[1] NPT
^[2] NPT, For 12,5 mm hose

Tipos de Mangueras

[HoseType]	[HoseSpecification]	[HoseTemperatureRange]	[HoseFittingDistribution]	[HoseFittingInlet]	[HoseConnectionDistribution]	[HoseConnectionInlet]
B	Cubierta de NBR/PVC y tubo interior de manguera de NBR. Trenzado de textil sintético	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2" + clip

Accessories

	Accesorio	No. De Artículo
	Pivoting bracket.	30372407
	Water gun in chromium plated brass. Max. temperature 95°C	30400110
	Water gun in stainless steel 316. Max. temperature 95°C	30400210
	Watergun EX in stainless steel 316. Max. temperature 95°C	30400211
	Water gun in stainless steel 316. Max. temperature 95°C	30400310
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl. coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl. coupl. 1/2(m)-3/4(f) SS	30432010

Accessories

	Accesorio	No. De Artículo
	Inlet kit for hose reel 1/2"	30511550
	Inlet kit for hose reel 3/8" with ball valve 3/8", 3/8"-3/8" adapter and 1/4" - 3/8" adapter.	30511650

Este contenido está protegido por la ley de derechos de autor, se proporciona únicamente con fines informativos y está sujeto a cambios sin previo aviso. © Nederman Holding AB

2025-12-04

6/7

Nederman

Hose Reel 883



