

# Suction hose PVC



## Suction hose PVC

✓ Temp. range: -20° to +70 °C.

Application areas: Robust oil-resistant hose, smooth inside. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease. Technical data:

# Suction hose PVC



---

[ProductStandards]

Designed for ISO 21904 compliance








---

Models

	Item no	Max vakuum (in. wg)	Diameter (in)	Length (ft)
	43822200 <sup>[1]</sup>	12,2	51	33
	43822300 <sup>[2]</sup>	12,2	51	82
	43822301 <sup>[1]</sup>		51	25
	43822600 <sup>[1]</sup>	12,2	51	25

<sup>[1]</sup> Couplings included, Ø 51 mm  
<sup>[2]</sup> Without couplers

## Accessories

	Accessory	Item no
	30M Vacuum Hose Storage Hanger - 4.5 in x 3 in (115 mm x 70 mm) for 1.5 in (38 mm) hose up to 16 ft (5 m)	40195450
	60M Vacuum Hose Storage Hanger - 6 in x 4.25 in (150 mm x 110 mm) for 1.5 in (38 mm) hose up to 33 ft (10 m)	40195451
	120M Vacuum Hose Storage Hanger - 8 in x 6.25 in (200 mm x 160 mm) for 1.5 in (38 mm) hose up to 66 ft (20 m)	40195452
	Floor Tool, Hose and Accessories Metal Wall Storage Rack - 21 in x 20 in x 12 in (542 mm x 490 mm x 305 mm)	40196370
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 85	40903030
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270