

L-PAK 150 Advanced

A compact stationary high vacuum unit with high filter efficiency and enhanced flexibility and advanced features



L-PAK 150 Advanced

- ✓ Easy to install
- ✓ Low noise level
- ✓ Low running and maintenance costs

The Nederman L-PAK offers the ideal solution for removing dust and fumes in all types of industries. Typical areas of applications can be found in welding shops, car body shops, construction industries, bakeries, industrial laundries, etc. The L-PAK is also perfect for cleaning of the workplace and the workshop floor. The L-PAK is easy to position and move due to its compact design, its low weight and the frame for fork lift handling. The integrated PLC-control ensure high functionality and can easily be updated with new functions. The automatic start/stop will save energy as well as extend the lifetime of the unit. The remote start/stop function makes it easy to ensure that everything is shut off when you go home from work.

Safe use

The duty idling and the temperature control functions reduce the risk of the fan getting overheated. There is also an indicator to show when service is required.

Unique and economic filter concept

The filter concept in L-PAK is unique as it combines high filter efficiency with long lifetime. A dynamic reducer separates coarse particles. Fine particles are separated on surface treated filter for a long lifetime. The PTFE fine filter is standard in the Advanced model but can easily be replaced by an antistatic filter if needed. You may also add a micro filter to filtrate even the finest particles.

Automatic filter cleaning as standard.

Continuous high performance is obtained by automatic filter cleaning (as standard). L-PAK uses filter cleaning by a short blast of reversed atmospheric air. By the rapid opening of a valve located on top of the filters, a powerful air pulse is created, efficiently dislodging dust from the filter socks.

Complete and ready to use

We can deliver complete installations but if you prefer to install your own system, this is very easy to do. Nederman can also offer a vast range of accessories like cleaning equipment, vacuum valves, swing arms and grinding tools with integrated fume and dust extraction.

The L-PAK Advanced models offers extra features such as improved sound insulation and enhanced functions in the PLC/control system that can handle extra external signals (DPS, BLI, pilot signal etc), adjustable cleaning cycle, start / stop timer functions etc.

L-PAK 150 Advanced

Certifikace	CE
Standard	Designed for ISO 21904 compliance
Instalace	Vnitřní
Metoda čištění filtru	Zpětný vzduchový proplach
Použití	Drť, Prach, Dýmy, Třísky, Granulát
Napětí (V)	400
Frekvence (Hz)	50
Počet fází	3
Typ filtru	Vak
Počet filtračních elementů	1
[ItemMaxAirFlow]	290
[ItemCapacityMax]	150 @ -15 kPa
[ItemMaxVacuum]	-22
Hmotnost (kg)	110
Výkon (kW)	3

Models

	Item number
	40051960

Accessories

	Accessory	Item number
	Microfilter D=140 x 350	40114110
	Filter pack P30/L-PAK150 PTFE	40119422
	Ochranný kryt výstupu výfuku o velikosti 100 mm (3,94 palce), který zabraňuje vniknutí ptáků a jiných malých zvířat do výfukového systému.	40130220
	90stupňový ohyb výstupu vzduchu, o velikosti 100 mm (3,94 palce), doporučený pro výfukové systémy, aby se přesměroval proud vzduchu a zabránilo se náhodnému vniknutí předmětů do sání.	40130820
	Řadový filtr stlačeného vzduchu zachycuje olej, vodu a pevné částice v přiváděném vzduchu a chrání ventily a další citlivé součásti před ucpaním nebo poškozením, zejména v prostředí, kde se normy kvality stlačeného vzduchu mohou lišit.	40620360
	Elektrická montážní sada poskytující rozbočovací skříňku pilotního signálu, která umožňuje připojení a odbočení více mikrospínačů z hlavního napájecího vedení.	40903520



Plastová vložka se snadno mění

mm (in)



