

L-PAK 250 Advanced

A compact stationary high vacuum unit with high filter efficiency and enhanced flexibility and advanced features



L-PAK 250 Advanced

- ✓ Easy to install
- ✓ Low noise level
- ✓ Low running and maintenance costs

The Nederman L-PAK offers the ideal solution for removing dust and fumes in all types of industries. Typical areas of applications can be found in welding shops, car body shops, construction industries, bakeries, industrial laundries, etc. The L-PAK is also perfect for cleaning of the workplace and the workshop floor. The L-PAK is easy to position and move due to its compact design, its low weight and the frame for fork lift handling. The integrated PLC-control ensure high functionality and can easily be updated with new functions. The automatic start/stop will save energy as well as extend the lifetime of the unit. The remote start/stop function makes it easy to ensure that everything is shut off when you go home from work.

Safe use

The duty idling and the temperature control functions reduce the risk of the fan getting overheated. There is also an indicator to show when service is required.

Unique and economic filter concept

The filter concept in L-PAK is unique as it combines high filter efficiency with long lifetime. A dynamic reducer separates coarse particles. Fine particles are separated on surface treated filter for a long lifetime. The PTFE fine filter is standard in the Advanced model but can easily be replaced by an antistatic filter if needed. You may also add a micro filter to filtrate even the finest particles.

Automatic filter cleaning as standard.

Continuous high performance is obtained by automatic filter cleaning (as standard). L-PAK uses filter cleaning by a short blast of reversed atmospheric air. By the rapid opening of a valve located on top of the filters, a powerful air pulse is created, efficiently dislodging dust from the filter socks.

Complete and ready to use

We can deliver complete installations but if you prefer to install your own system, this is very easy to do. Nederman can also offer a vast range of accessories like cleaning equipment, vacuum valves, swing arms and grinding tools with integrated fume and dust extraction.

The L-PAK Advanced models offers extra features such as improved sound insulation and enhanced functions in the PLC/control system that can handle extra external signals (DPS, BLI, pilot signal etc), adjustable cleaning cycle, start / stop timer functions etc.

L-PAK 250 Advanced

Certificeringen	CE
Standaard	Designed for ISO 21904 compliance
Installatie	Binnen
Filter reinigingsmethode	perslucht retour
Applicatie	Grit, Stof, Dampen, Spaanders, Granulaten
Voltage (V)	400
Frequentie (Hz)	50
Aantal fase	3
Filtertype	Zakken filter
Aantal filterelementen	1
Max. luchtstroom (m³/h)	420
[ItemCapacityMax]	250 @ -15 kPa
Max. vacuüm	-21
Gewicht (kg)	140
Vermogen (kW)	5,5

Modellen

	Artikelnummer
	40051860

Accessoires

	Accessoires	Artikelnummer
	Filter package 1,6m2 PTFE	40114440
	Filter pack 1,6m2 antistat	40114190
	Gebogen uitlaatbuis van 90 graden, Ø100 mm, aanbevolen voor uitlaatsystemen om de luchtstroom om te leiden en te voorkomen dat er per ongeluk voorwerpen in de inlaat terechtkomen.	40130820
	Beschermende uitlaatklep van Ø100 mm om te voorkomen dat vogels en andere kleine dieren het systeem binnendringen.	40130220
	Microfilter D= 140 x 500	40114120
	Elektrische montageset met een aansluitdoos voor een pilotsignaal, waarmee meerdere microschakelaars op de hoofdstroomlijn kunnen worden aangesloten en afgetakt.	40903520
	Inline-persluchtfilters vangen olie, water en vaste deeltjes op in de binnenkomende lucht en beschermen kleppen en andere gevoelige componenten tegen verstopping of schade, met name in omgevingen waar de kwaliteitsnormen voor perslucht kunnen variëren.	40620360



The plastic bin liner is easy to change

mm (in)



