

Industrial vacuum cleaner 55 S

Dry vacuum cleaner useful in most applications with dust from tools or cleaning operations within industry



The 55S is a efficient three phase compact industrial vacuum cleaner. A very efficient, economical, low noise level and easy to handle dry vacuum. The vacuum is very easy to dismantle and clean. This portable dust collector has long filter lifetime 4-6000 h (with bag filter). The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.

- Long filter lifetime (4-6000 hours)
- Low noise level
- Micro filter as option

Product name	Industrial vacuum cleaner 55 S
Noise level (dB(A))	72
Protection class	IP 55
Filter efficiency (%)	99
Installation	Indoor
Material	Casing in sheet metal
Filter cleaning method	Reverse air pulse
Application	Dust, Granulate, Fumes, Swarf
Working pressure (kPa)	30
Dustbin volume (l)	28
Max Airflow (m ³ /h)	360
Hose Diameter (mm)	51
Hose length (m)	5
No of phases	3
Filter type	Bag
Number of filter elements	1
Filter material	
Noise level (dB(A))	
Max vacuum (kPa)	30
Weight (kg)	101
Hose length (m)	
Hose diameter (mm)	



Granulate Fumes Swarf Dust

Industrial vacuum cleaner 55 S

Image	Power Voltage (V)	Frequency (Hz)	Power (kW)	Model
	400	50	5,5	40056000*
	230	60	6,3	40056030*
	460	60	6,3	40056040*
	400	50	5,5	40056060**

*Heavy duty cleaning equipment included

**Heavy duty cleaning equipment included. Antistatic filter and micro filter included

Industrial vacuum cleaner 55 S

	Accessory	Part No
	Microfilter D= 140 x 500	40114120
	Hand nozzle, hard brush Ø90mm, Ø51	43860001*
	Hand nozzle, soft brush Ø90 mm	43860200*
	Toothed nozzle width 130 mm, Ø51	43861001**
	Cone nozzle Length 250 mm, Ø51	43862001***
	Scraper nozzle, length: 1000 mm Ø51	43851150**
	Scraper nozzle, length: 500 mm Ø51	43851050**
	Bulk nozzle Length 910 mm, Ø51	43850001*
	Bulk nozzle for floor with handle length 1200 mm, Ø51 mm	43850150**
	Filter package 1,6m2 PTFE	40114440
	Filter pack 1,6m2 antistat	40114190

*ATEX - Suitable for combustible dust (zone 20,21,22). Ensure earthing to extraction unit. Not to be used in combustible gas atmospheres or extraction of explosive materials.

**ATEX - Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA, IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials

***ATEX - Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA, IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials.